

PRELIMINARY DATA SHEET

OLC049: Radiation-Tolerant, Phototransistor Surface-Mount Optocoupler

Features

- Miniature non-hermetic surface-mount package
- Radiation tolerant
- High CTR guaranteed over $-55\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ ambient temperature range
- 1000 V_{bc} electrical isolation

Description

The OLC049 is specifically designed for large satellite constellation applications that require optical isolation in radiation environments such as gamma, neutron, and proton radiation with a high Current Transfer Ratio (CTR) and low saturation V_{CE}. Each optocoupler consists of an LED and N-P-N silicon phototransistor that is electrically isolated, but optically coupled inside a non-hermetic, four-pin Leadless Chip Carrier (LCC) package.

Electrical parameters are similar to the JEDEC registered 4N49U optocoupler, but with better CTR degradation characteristics due to radiation exposure. The hermetic surface-mount variant of the OLC049 optocoupler is available as the OLS049, both in a non-screened catalog version as well as a high-reliability screened version.

The device mounting for the OLC049 is achieved with reflow soldering or conductive epoxies.




Figure 1. OLC049 Block Diagram

A functional block diagram of the OLC049 is shown in Figure 1. The absolute maximum ratings of the OLC049 are provided in Table 1. Electrical specifications are provided in Table 2.

Typical performance characteristics of the OLC049 are illustrated in Figures 2 through 4. A typical switching test circuit is shown in Figure 5 and package dimensions for the OLC049 are provided in Figure 6.

Table 1. OLC049 Absolute Maximum Ratings¹

Parameter	Symbol	Minimum	Maximum	Units
<i>Coupled</i>				
Input to output isolation voltage ²	V _{DC}	-1000	+1000	V
Storage temperature range	T _{STG}	-65	+150	°C
Operating temperature range	T _A	-55	+125	°C
Soldering temperature (heated collet, 5 seconds)			260	°C
Soldering temperature (vapor phase reflow, 30 seconds)			215	°C
<i>Input Diode</i>				
Average input current	I _{DD}		40	mA
Peak forward current (≤1 ms duration)	I _F		1	A
Reverse voltage	V _R		2	V
Power dissipation ³	P _D		60	mW
<i>Output Detector</i>				
Collector to emitter voltage	V _{CE}		60	V
Emitter to collector voltage	V _{EC}		5	V
Continuous collector current	I _{CC}		50	mA
Power dissipation ⁴	P _D		300	mW

¹ Exposure to maximum rating conditions for extended periods may reduce device reliability. There is no damage to device with only one parameter set at the limit and all other parameters set at or below their nominal value. Exceeding any of the limits listed here may result in permanent damage to the device.

² Measured between pins 1 and 4 shorted together, and pins 2 and 3 shorted together. T_A = 25 °C and duration = 1 s.

³ Derate linearly at 1 mW/°C above 65 °C.

⁴ Derate linearly at 3 mW/°C above 25 °C.

ESD HANDLING: *Although this device is designed to be as robust as possible, electrostatic discharge (ESD) can damage this device. This device must be protected at all times from ESD when handling or transporting. Static charges may easily produce potentials of several kilovolts on the human body or equipment, which can discharge without detection. Industry-standard ESD handling precautions should be used at all times.*

Table 2. OLC049 Electrical Specifications¹
(T_A = 25 °C, Unless Otherwise Noted)

Parameter	Symbol	Test Condition	Min	Max	Units
On-state collector current	I _{C_ON}	I _F = 1 mA, V _{CE} = 5 V I _F = 2.0 mA, V _{CE} = +5.0 V, T _A = -55 °C I _F = 2 mA, V _{CE} = 5 V, T _A = 100 °C	2 +2.8 2	12	mA
Saturation voltage	V _{CE_SAT}	I _F = 2.0 mA, I _C = 2.0 mA		0.3	V
Breakdown voltage: Collector to emitter Emitter to collector	BV _{CEO} BV _{ECO}	I _{CE} = 1 mA I _{EC} = 100 μA	60 5		V
Leakage current, collector to emitter	I _{CE_OFF}	V _{CE} = 20 V V _{CE} = 20 V, T _A = 100 °C		100 100	nA μA
Input: Forward voltage	V _F	I _F = 10.0 mA, T _A = -55 °C I _F = 10.0 mA I _F = 10.0 mA, T _A = 100 °C	+1.4 1.2 1.1	+2.0 1.8 1.7	V V V
Reverse current	I _R	V _R = 2 V		100	μA
Output resistance ²	R _{L_0}	V _{L_0} = ±1000 V _{DC}	10 ¹¹		Ω
Output capacitance ²	C _{L_0}	V _{L_0} = 0 V, f = 1 MHz		5	pF
Time: Rise Fall	t _r t _f	V _{CC} = 10 V, R _L = 100 Ω I _F = 10 mA		25 25	μs μs

¹ Performance is guaranteed only under the conditions listed in the above table.

² Measured between pins 1 and 4 shorted together, and pins 2 and 3 shorted together. T_A = 25 °C and duration = 1 s.

Typical Performance Characteristics
 (TA = -55 °C to +125 °C, Unless Otherwise Noted)




Figure 2. Forward Current vs Forward Voltage




Figure 3. Normalized Collector Current vs Forward Current




Figure 4. Normalized CTRce vs Temperature





Figure 5. OLC049 Switching Test Circuit



NOTES:

1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.
2. METALIZATION PULL BACK FROM SUBSTRATE EDGE: 0.002 MAXIMUM.
3. UNLESS SPECIFIED DIMENSIONS ARE SYMMETRICAL ABOUT CENTER LINES.

Figure 6. OLC049 Package Dimensions

Ordering Information

Model Name	Manufacturing Part Number
OLC049: Radiation-Tolerant, Phototransistor Non-hermetic Surface-Mount Optocoupler	OLC049

Copyright © 2020 Isolink, Inc. All Rights Reserved.

Information in this document is provided in connection with Isolink, Inc. ("Isolink"), a wholly-owned subsidiary of Skyworks Solutions, Inc. These materials, including the information contained herein, are provided by Isolink as a service to its customers and may be used for informational purposes only by the customer. Isolink assumes no responsibility for errors or omissions in these materials or the information contained herein. Isolink may change its documentation, products, services, specifications or product descriptions at any time, without notice. Isolink makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Isolink assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of Isolink products, information or materials, except as may be provided in Isolink Terms and Conditions of Sale.

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. ISOLINK DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. ISOLINK SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Customers are responsible for their products and applications using Isolink products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Isolink assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Isolink products outside of stated published specifications or parameters.

Isolink is a trademark of Isolink Inc. in the United States and other countries. Skyworks and the Skyworks symbol are trademarks or registered trademarks of Skyworks Solutions, Inc., in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners.